

Body Specifications		16 yd <sup>3</sup>	20 yd <sup>3</sup>	22 yd <sup>3</sup>	24 yd <sup>3</sup>	26 yd <sup>3</sup>	30 yd <sup>3</sup>	32 yd <sup>3</sup>
Body Capacity	yd <sup>3</sup>	16	20	22	24	26	30	32
	m <sup>3</sup>	12.2	15.3	16.8	18.4	19.9	22.9	24.5
Hopper Capacity	yd <sup>3</sup>	3	3	3	3	3	3	3
	m <sup>3</sup>	2.3	2.3	2.3	2.3	2.3	2.3	2.3
Overall Length*	in.	194	218	239	248	269	281	293
	mm	4928	5537	6071	6299	6833	7137	7442
Overall Length (Tailgate Raised)*	in.	224	248	254	278	284	309	321
	mm	5690	6299	6452	7061	7214	7849	8153
Overall Width	in.	96	96	96	96	96	96	96
	mm	2438	2438	2438	2438	2438	2438	2438
Overall Height Above Frame	in.	97	97	97	97	97	109	109
	mm	2464	2464	2464	2464	2464	2769	2769
Loading Sill Height Above Frame	in.	68	68	68	68	68	68	68
	mm	1727	1727	1727	1727	1727	1727	1727
Mounted Weight (route ready)	lbs.	10,400	11,000	11,200	12,000	12,200	13,200	13,600
	kg.	4718	4990	5081	5444	5534	5988	6170
Compaction Ratio	Up to 700 lbs per yd <sup>3</sup>							
* Including 30 in. for lift mount								