



Street Flushers

Patented water control system – constant water pressure



Etnyre Street Flushers with Hydrostatically Driven Water Pumps (auxilliary engine driven water pumps available)

- Patented Etnyre water control system automatically maintains a predetermined water pressure while flushing.
- Hydrostatic water pump drive reduces maintenance and allows adjustment to meet job requirements.
- Light weight design and improved weight distribution for larger payloads and increased productivity.



Two Styles to Choose from...

Standard Not Skirted

- Standard unit with capacities of 1900, 2200, 2500 gallons (for 120"/126" C.A. truck mounting), and 2700, 3000, 3500 gallons (for 120"/126" C.B. truck mounting).
- 750 G.P.M. water pump with hydrostatic drive.
- Three flushing nozzles with pilot operated 2" globe type valves.



with Optional Skirting

- Includes the same features as our standard Flusher plus skirting and an enclosed compartment with rear access doors.



Etnyre offers a wide variety of additional options and accessories.

For additional information on Etnyre Street Flushers, request the following information:
A-801-** Street Flusher Features.

E. D. Etnyre & Co., whose policy is one of continuous improvement, reserves the right to change specifications without notice. Photos and illustrations contain standard and optional equipment.



E. D. ETNYRE & CO.,

1333 South Daysville Road, Oregon, Illinois 61061
Phone: 800-995-2116 or 815/732-2116 • Fax 815-732-7400
www.etnyre.com • e-mail: sales@etnyre.com

Litho in U.S.A. Supersedes L-801-96 **L-801-99**